



INFINITY MIB-2M

Specification

MODEL INFINITY MIB-2M

CAMERA SPECIFICATION	
Resolution	1080P
Image sensor	F23
Main processor	3516EV200
Effective pixels	1920 X 1080P
TV System	PAL/NTSC
Elcetronic shutter system	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync system	External
Usable illumination	0.01Lu
S/N ratio	≥52dB
Scanning system	Progressive
Video Output	Network

LENS	
Focus lens	3.6mm
Focus control	Fixed
Lens type	Fixed
Pixels	1080P

NIGHT VISION	
Infrared LED	IR led φ 12X24PCS / 14μ*18PCS
Infrared distance	20M~25M
IR status	Under 10 Lux By CDS
IR power ON	CDS Auto Control

NETWORK	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support Onvif 2.4
P2P	YES, Support QR Code
POE	Support
WIFI	N/A
Video delay	0.35 (Within the lan)
Smart phone	Iphone, Ipad, Android, Android Pad
Main stream	1920 x 1080P
Sub stream	704 x 576 - 352 x 288
IE browser	IE6-11

CAMERA FEATURE	
Day/Night	Color / B&W (IR-CUT)
Compression	H.264/H.265
Image config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion detection	Support
Privacy masking	3 Rectangular Zone
DWDR / WDR	YES
Recording mode	NVR/NAS/CMS/WEB
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German,Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

GENERAL	
Housing	Metal
Bracket	YES
IR cut filter	Yes
Operation temperature	-10 - +50 RH95% Max
Storage temperature	-20 - +60 RH95% Max
Power source	DC12V±10%, 1000mA
Dimension	151 x 50 x 50 mm
Weight	0.45 Kg

Key Feature

- Resolution up to 2.0 Mega Pixel
- Infrared LED 20M
- ONVIF Support ONVIF 2.4
- Metal Casing
- Support PoE
- H.265 compression
- 3.6mm fixed lens
- IP66