

## INFINITY DDV-8N408/16-H2EA



### Key Feature

- H.265 Pro+/H.265 Pro/H.265 video compression
- HDTV/1/AHD/CVI/CVBS/IP video input
- Audio via coaxial cable
- Up to 8/16-ch IP camera inputs (up to 8 MP)
- Max. 800 m for 1080p and 1200 m for 720p HDTV signal transmission
- Up to 10 TB capacity per HDD

### Specification

Model	DDV-8N408-H2EA	DDV-8N416-H2EA
<b>Recording</b>		
<b>Video compression</b>	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	
<b>Encoding resolution</b>	When 8 MP Lite mode is not enabled: 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF When 8 MP Lite mode is enabled: 8 MP Lite/3MP/1080P/720P/WD1/4CIF/VGA/CIF	
<b>Frame rate</b>	Main stream: When 8 MP Lite mode is not enabled: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) *: 8 MP@8 fps is only available for channel 1 of DDV-8N408-H2EA When 8 MP Lite mode is enabled: 8 MP Lite/3MP/1080P/720P/WD1/4CIF/VGA/CIF@15 fps *: 8 MP Lite is only available for DDV-8N408-H2EA Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N)	
<b>Video bit rate</b>	32 Kbps to 10 Mbps	
<b>Dual stream</b>	Support	
<b>Stream type</b>	Video, Video & Audio	
<b>Audio compression</b>	G.711u	
<b>Audio bit rate</b>	64 Kbps	
<b>Video and Audio</b>		
<b>IP video input</b>	8-ch (up to 16-ch) Up to 8 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras	16-ch (up to 32-ch)
<b>Analog video input</b>	8-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection	16-ch
<b>HDTV input</b>	8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25	
<b>AHD input</b>	5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30	
<b>HDCVI input</b>	5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30	
<b>CVBS input</b>	PAL/NTSC	
<b>CVBS output</b>	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480	
<b>VGA output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
<b>HDMI output</b>	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
<b>Audio input</b>	4-ch, RCA (2.0 Vp-p, 1 KΩ)	
<b>Audio output</b>	1-ch, RCA (Linear, 1 KΩ)	
<b>Two-way audio</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)	
<b>Synchronous playback</b>	8-ch	16-ch

Network		
<b>Remote connection</b>	64	128
<b>Network protocol</b>	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF	
<b>Network interface</b>	1, RJ45 10M/100M self-adaptive Ethernet interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
<b>Auxiliary interface</b>		
<b>SATA</b>	2 SATA interfaces	
<b>Capacity</b>	Up to 10 TB capacity for each disk	
<b>Serial interface</b>	RS-485 (half-duplex)	
<b>USB interface</b>	2 × USB 2.0	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 3.0
<b>Alarm in/out</b>	8/4	16/4
<b>General</b>		
<b>Power supply</b>	12 VDC	
<b>Consumption (without HDD)</b>	≤ 20 W	≤ 25 W
<b>Working temperature</b>	-10 °C to +55 °C (+14 °F to +131 °F)	
<b>Working humidity</b>	10% to 90%	
<b>Dimension (W × D × H)</b>	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)	
<b>Weight (without HDD)</b>	≤ 1.78 kg (3.9 lb)	≤ 2 kg (4.4 lb)